

What is claimed:

1. (Currently amended) An all-in-one prophy angle comprising:

an angled prophy handpiece with a driveshaft with first and second ends, the first driveshaft end is mounted to an electrical or air driven dental handpiece;

an elastomeric dental prophy cup with a longitudinal axial direction, a rear end and a front end with a front polishing portion, an inside and an outside wherein the rear end of the prophy cup is attached to the second driveshaft end of the angled prophy handpiece; and

a solid core prophy paste with a longitudinal axial direction, a front end and a rear end wherein the solid core prophy paste is contained longitudinally within the inside of the prophy cup.

2. (Currently amended) An all-in-one prophy angle as in claim 1 wherein the prophy cup front end ~~defines a skirt which flares outwardly towards the front end, the skirt~~ front end is used for polishing the teeth.

3. (Original) An all-in-one prophy angle as in claim 1 wherein an annular retaining lip defines the inside of the front end of the prophy cup, the lip retains the solid core prophy paste within the inside of the prophy cup.

4. (Original) An all-in-one prophy angle as in claim 1 wherein the solid core paste is defined by circumferential parallel rings positioned at a right angle to the prophy paste's longitudinal axis, the grooves are sized to fit the annular retaining lip which, when seated in the annular groove, retains the prophy paste within the prophy cup.

5. (Original) An all-in-one prophy angle as in claim 1 wherein the force means is a spring with a front end and a rear end positioned between the inside rear end of the prophy cup and the rear end of the solid core prophy paste, the spring applying force to the solid core which holds the solid core against the tooth surface during use of the prophy angle.

6. (Original) An all-in-one-prophy angle as in claim 1 wherein a cylindrical piston is fitted to the inside diameter of the prophy cup and is positioned between the rear end of the solid core prophy paste and the front end of the spring.

7. (Cancelled).

8. (Original) An all-in-one prophylaxis angle as in claim 1 wherein the elastomeric prophylaxis cup is comprised of natural rubber or polyisoprene, both with a durometer hardness value of about 40 to about 70.

9. (Original) An all-in-one prophylaxis angle as in claim 1 wherein the elastomeric prophylaxis cup contains an abrasive such as pumice or minerals which creates a polishing effect on the tooth surface during the use of the prophylaxis cup.

10. (Currently amended) An all-in-one prophylaxis angle comprising:

a prophylaxis angle with containing a driveshaft with first and second ends, the first driveshaft end is

attached to power source;

a hollow 2-6 mm diameter second driveshaft end;

an elastomeric dental prophylaxis cup with a longitudinal axial direction, a rear end and a front end with a front polishing portion, an inside and an outside wherein the rear end of the prophylaxis cup is attached to the second driveshaft end of the angled prophylaxis handpiece;

a solid core prophylaxis paste with a longitudinal axial direction, a front end and a rear end wherein the solid core prophylaxis paste is contained longitudinally within the inside of the prophylaxis cup the paste extends from the front of the prophylaxis cup into the hollow interior of the prophylaxis drive shaft; and

a force means which applies pressure to the rear end of the solid core prophylaxis paste.

11. (Original) An all-in-one prophylaxis angle as in claim 10 wherein the prophylaxis cup front end defines a skirt which flares outwardly towards the front end, the skirt is used for polishing the teeth.

12. An all-in-one prophylaxis angle as in claim 10 wherein an annular retaining lip defines the inside of the front end of the prophylaxis cup, the lip retains the solid core prophylaxis paste within the inside of the prophylaxis cup.

13. (Original) An all-in-one prophylaxis angle as in claim 10 wherein the solid core paste is defined by circumferential parallel rings positioned at a right angle to the prophylaxis paste's longitudinal axis, the grooves are sized to fit the annular retaining lip which, when seated in the annular groove, retains the prophylaxis paste within the prophylaxis cup.

14. (Original) An all-in-one prophy angle as in claim **10** wherein the force means is a spring with a front end and a rear end positioned between the inside rear end of the prophy cup and the rear end of the solid core prophy paste, the spring applying force to the solid core which holds the solid core against the tooth surface during use of the prophy angle.

15. (Original) An all-in-one-prophy angle as in claim **10** wherein a cylindrical piston is fitted to the inside diameter of the prophy cup and is positioned between the rear end of the solid core prophy paste and the front end of the spring.

16. (Cancelled).

17. (Original) An all-in-one prophy angle as in claim **10** wherein the elastomeric prophy cup is comprised of natural rubber or polyisoprene, both with a durometer hardness value of about 40 to about 70.

18. (Original) An all-in-one prophy angle as in claim **10** wherein the elastomeric prophy cup contains an abrasive such as pumice or minerals which creates a polishing effect on the tooth surface during the use of the prophy cup.

19. (Currently amended) An all-in-one prophy angle comprising:

a prophy angle with an internal containing a driveshaft with first and second ends, the first driveshaft end is attached to power source;

a hollow 2-6 mm diameter second driveshaft end;

an elastomeric dental prophy cup with a longitudinal axial direction, a rear end and a front end with a front polishing portion, an inside and an outside wherein the rear end of the prophy cup extends and is contained within the second end driveshaft hollow interior;

a solid core prophy paste with a longitudinal axial direction, a front end and a rear end wherein the solid core prophy paste is contained longitudinally within the inside of the prophy cup the paste extends from the front of the prophy cup into the hollow interior of the prophy drive shaft; and

a force means which applies pressure to the rear end of the solid core prophy paste.

20. (Currently amended) An all-in-one prophy angle as in claim **19** wherein the prophy cup front end defines a skirt which flares outwardly towards the front end, the skirt front end is used for polishing the teeth.

21. (Original) An all-in-one prophy angle as in claim **19** wherein an annular retaining lip defines the inside of the front end of the prophy cup, the lip retains the the solid core prophy paste within the inside of the prophy cup.

22. (Original) An all-in-one prophy angle as in claim **19** wherein the solid core paste is defined by circumferential parallel rings positioned at a right angle to the prophy paste's longitudinal axis, the grooves are sized to fit the annular retaining lip which, when seated in the annular groove, retains the prophy paste within the prophy cup.

23. (Original) An all-in-one prophy angle as in claim **19** wherein the force means is a spring with a front end and a rear end positioned between the inside rear end of the prophy cup and the rear end of the solid core prophy paste, the spring applying force to the solid core which holds the solid core against the tooth surface during use of the prophy angle.

24. (Original) An all-in-one-prophy angle as in claim **19** wherein a cylindrical piston is fitted to the inside diameter of the prophy cup and is positioned between the rear end of the solid core prophy paste and the front end of the spring.

25. (Cancelled).

26. (Original) An all-in-one prophy angle as in claim **19** wherein the elastomeric prophy cup is comprised of natural rubber or polyisoprene, both with a durometer hardness value of about 40 to about 70.

27. (Original) An all-in-one prophy angle as in claim **19** wherein the elastomeric prophy cup contains an abrasive such as pumice or minerals which creates a polishing effect on the tooth surface during the use of the prophy cup.

28. (Original) An all-in-one prophy angle as in claim **19** wherein the prophy angle is comprised of internal rotational paddles which propel air or a liquid when the prophy angle is run, the air or liquid provides the extruding force means against the solid core prophy paste.